IMAGING **VDISPLAY**

31" Beacon **Double Sided Backlit**

Trim: 31"w x 85"h Visual Area: 31"w x 78"h

This pdf template is set up at 100% file s Please keep your file at 100%.

We accept both CMYK and RGB color m You can change the color mode in Illustra

If pms color match is important, please r Pantone Solid Coated spot colors. Let yo rep know that color match is important.

Benchmark is a fully "color managed" sh Best results come from profiled images.

Raster images should be 150 to 200 dpi at size. If you embed your images in Illustration can zoom in to check the quality. If you s edges or j-peg artifacts in your Illustraton you'll see them in your final printed grap

Please keep all text 1" from all sides. Please include bleed.

Please supply all fonts, or you can select a and convert to outlines before sending th for printing.

Please check that all placed images are su or embedded in your file.

Call your sales rep with any questions or concerns. 847-290-0002

DO NOT FLATTEN FIL

Benchmark Imaging & Display 221 Lively Blvd. Elk Grove Village, IL 60007

847-290-0002 www.benchmarkimaging.com

size.		
node.		
ator.		
ΠΓΔ		
our sales		
hop.		
at final		
rator, you		
see ragged		
or file,		
phic.		
all text		
ne file		
supplied		
	Trim	
	Bleed	
		Banner Foot - extends into hardware

31" width

Banner Foot - extends into hardware top of foot area is visible (~2"). We recommend extending background through to trim.

Banner head: covered by hardware, please extend the background to bleed.

Maximun live area: 78" h

Please add at least 2-3" bleed to the bottom of your live area. The top of the foot area is visable.



Bleed